2024 **MULE PRO-FXR[™] 1000**





7.9 gal

14.0 ft

3

2,000 lb

122.0 in

64.0 in

77.2 in

37.6 x 53.3 x 11.0 in

999 lb / 600.0 lb CA Model

1,616.3 lb / 1,263.5 lb CA Model

(2) Halogen headlights. (2) LED headlights



POWER

Engine	4-stroke, 2-cylinder, DOHC, liquid-cooled, gas
Displacement	999cc
Maximum Torque	61.5 lb-ft
Bore x Stroke	92.0 x 75.1mm
Compression Ratio	10.1:1
Fuel System	DFI® with 38mm throttle body
Transmission	Continuously Variable Transmission (CVT) with (L,H,N,R)
Final Drive	Selectable 2WD/4WD, shaft Dual mode rear differential with differential lock
Engine Braking	Yes
Alternator Output (max)	90 amp

CAPARII ITV

GAFADILITI			
		Curb Weight	1,735.3 lb* / 1,737.5 lb* CA Model
Front Suspension / Wheel Travel	Double wishbone/11.0 in	Wheelbase	79.7 in
Rear Suspension / Wheel Travel	Double wishbone/10.1 in	Instruments	Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator,
Front Tires	27 x 9.00-12, radial		oil pressure warning indicator, fuel injection warning indicator, CVT and EPS warning indicators, neutral, reverse
Rear Tires	27 x 11.00-12, radial		and parking indicators, seatbelt reminder lamps
Steering	Electric Power Steering (EPS), Tilt steering	Wheel Type	Alloy
Front Brakes	Dual Disc, 2 piston caliper	Additional Features	Rear Bumper, Contoured Two-Tone Bench Seat
Rear Brakes	Dual Disc, 1 piston caliper	Color Choices	Metallic Sierra Blue
Park Brake Type	Independent, Mechanical Disc	Warranty	Kawasaki STRONG 3-Year Limited Warranty
Ground Clearance	13.2 in (max), 12.2 in (std)	Kawasaki Protection Plus™ (optional)	12, 24, 36, or 48 months

*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

Fuel Capacity

Turning Radius

Dimensions (LxWxH) **Cargo Bed Load**

Payload Capacity

Seating Capacity

Towing Capacity

DETAILS

Overall Length

Overall Width

Overall Height

Cargo Bed

Capacity

Lighting

All MULETM PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE[™] side x side is an off- highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2024 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.

Scan with camera to view videos, key features and more.



Let the Good Times Roll