

2024

NINJA[®] ZX[™]-6R



MSRP NON-ABS

\$11,399

MSRP ABS

\$12,399

-  METALLIC FLAT SPARK BLACK/EBONY
-  PEARL ROBOTIC WHITE/METALLIC GRAPHITE GRAY



POWER		Front Brakes	
Engine	4-stroke, In-Line Four, DOHC, 16-valve, liquid-cooled	Dual semi-floating 310mm discs with dual radial-mounted, monobloc, opposed 4-piston caliper, Kawasaki Intelligent anti-lock Brake System (KIBS) (ABS only)	
Displacement	636cc	Rear Brakes	
Bore x Stroke	67.0 x 45.1mm		
Compression Ratio	12.9:1	Single 220mm petal discs with single-piston caliper, Kawasaki Intelligent anti-lock Brake System (KIBS) (ABS only)	
Fuel System	DFI [®] with 38mm Keihin throttle bodies (4) and oval sub-throttles	DETAILS	
Ignition	TCBI with Electronic Advance	Frame Type	Aluminum perimeter
Transmission	6-speed, return shift	Rake/Trail	23.5° / 4.0 in
Final Drive	Sealed chain	Overall Length	79.7 in
Electronic Rider Aids	Kawasaki Traction Control (KTRC), Power Modes (Full/Low), Kawasaki Intelligent anti-lock Brake System (KIBS) (ABS only), Kawasaki Quick Shifter (KQS) (upshift only)	Overall Width	28.0 in
PERFORMANCE		Overall Height	43.3 in
		Ground Clearance	5.1 in
Front Suspension / Wheel Travel	41mm inverted fork (SFF-BP) with rebound and compression damping and spring preload adjustability, and top-out springs / 4.7 in	Seat Height	32.7 in
Rear Suspension / Wheel Travel	Bottom-link Uni-Trak [®] with gas-charged shock, stepless compression damping adjustment, stepless adjustable rebound damping, fully adjustable spring preload / 5.9 in	Curb Weight	436.6 lb* (ABS), 432.2 lb* (non-ABS) 50-State Model, 434.4 lb* (ABS), 430.0 lb* (non-ABS) 49-State Model
Front Tire	120/70 ZR17	Fuel Capacity	4.5 gal
Rear Tire	180/55 ZR17	Wheelbase	55.1 in
		Special Features	4.3" Full-Color TFT Instrumentation, Smartphone Connectivity via RIDELOGY THE APP
		Color Choices	Lime Green/Ebony
		Warranty	12 Month Limited Warranty
		Kawasaki Protection Plus [™] (optional)	12, 24, 36 or 48 months

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2024 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit [Kawasaki.com](https://www.kawasaki.com) for full product details.